

Instructions for using airdry DUO

Instructions for use:

Remove the outer plastic bags to activate airdry DUO. The upper side of airdry DUO is made from a non-woven fabric which becomes noticeably damp through moisture absorption. The underside is made of plastic, preventing moisture from being transferred downwards.

Place the bags, plastic side down, in a suitable location in the vehicle. Weigh the bag to determine whether the saturation limit of 1.1 kg per bag has been reached.

Please note: airdry DUO can slip while driving. Before setting off, protect vehicle occupants and other road users by placing airdry DUO where it cannot slide around or enter the driver's footwell.

Regeneration:

airdry DUO can be placed on a radiator or in an airing cupboard to dry and regenerate. airdry DUO releases its moisture over an extended period of time. This may take a few days or weeks depending on saturation. After regeneration, a dry weight of approximately 700 g per bag is to be expected.

How it works:

Breathing, ventilation, heating, air conditioning and external influences such as rain and sunlight cause extreme air changes in vehicles within minutes, often resulting in condensation and misted windows. airdry DUO responds by continuously absorbing excess moisture from the air.

Like a sponge, airdry draws and then locks in moisture using the contained action granules. The two-bag airdry DUO can be optimally positioned in different sections of the vehicle, creating a dual action effect. airdry DUO is odourless.

We recommend placing both airdry bags inside the vehicle at the same time, preferably near the front windscreen.

Windows quickly clear or do not mist up at all.

Up to 1000 ml water is absorbed through the surface of the product. Depending on vehicle size, temperature and prevailing humidity airdry DUO is effective for up to five months. After this time or when each bag reaches a weight of 1.1 kg, it is important to restore airdry DUO to its unsaturated weight of approx. 700 g per bag.

