

Instructions for use

Multi Dry universal dehumidifier

Operation manual

Multi Dry

Multi Dry is activated by removing the protective film. For safety reasons (moisture transfer), avoid direct contact with liquid-absorbing and rust-prone products (fabric, paper, metal). For example, use a saucer when placing on a carpet. The degree of saturation (max. 1.6 kg) can be determined by weighing.

Regeneration

Multi Dry

Multi Dry can be dried in an oven (no microwave) or on a heater for reuse. For oven drying, place Multi Dry on a rack at a medium height and set the oven temperature to approx. 70 - 80°C. Higher temperatures can damage the bag fleece (no risk of fire). The drying process takes approx. 4-5 hours. If Multi Dry is dried on a radiator, the drying process takes several days.

Warning: There is a risk of burns when touching the heated bag and especially the metal clamp. Use oven mitts or protective gloves when removing from the oven.

Product contains salt - avoid eye contact.

How it works

Multi Dry

Multi Dry removes the excess moisture from the air. Mould, rust, mildew stains and musty smells are prevented. The moisture is absorbed in the storage granulate (no dripping system). Multi Dry can absorb up to 600 g of water. Multi Dry is odourless. The dehumidification function is effective for approx. 35 m³ for 2-4 months, depending on the humidity and temperature. At a harmful relative humidity above approx. 60 percent, Multi Dry absorbs moisture. When the air is dry, the moisture is released again. It therefore only works when the humidity is too high, and has a balancing effect on the room climate when the humidity changes..

