

Instructions for use

airdry Safe Dry dehumidifier

Operation manual



Take the black dehumidifier pad and the indicator out of the foil bag. Slide the indicator into the narrow slot on the back of the box with the printed side facing outwards so that the blue coloured dot is visible in the window.

Place the dehumidifier pad back in the box, making sure that the fleece side through which the moisture penetrates is on the side with the holes. Place the Safe Dry in the room or cupboard to be protected so that the holes are not covered. These serve to better absorb moisture.

From time to time, compare the colour dot in the window with the colour dots above and below it. If the colour dot in the window has turned pink, the dehumidifier pad should be weighed. If the dehumidifier weighs more than 450 g, it should be replaced or regenerated.

Product contains salt. Avoid contact between the top of the cushion and metal, leather and other sensitive materials. Do not destroy fleece bag. Avoid eye contact.

Regeneration



Safe Dry can be dried on a heater for renewed use. To do this, remove the dehumidifier pad from the box and place it with the foil side on the heater. Safe Dry releases the stored moisture over a longer period of time, which can be days or weeks depending on saturation and heating. Drying to a weight of approx. 330 g can be expected.

How it works



As soon as the foil bag is removed, the Safe Dry becomes active. Like a magnet, it draws the moisture out of the air until a relative humidity of less than 60 % is reached. This prevents rust, mould and musty smells. Up to 180 g of water are absorbed and stored. As soon as the Safe Dry is saturated and the ambient air is too humid, the humidity indicator changes colour from blue to pink.



Rev.03

